



## EXPRESSIONS REVOLUTION

<b>PRODUCT DESCRIPTION</b>	Expressions Revolution is an environmentally friendly, pure acrylic emulsion based interior decorative coating, designed for beautiful broken silky pearl colour effects. The attractive and graceful finish creates an artistic and elegant look. It offers excellent adhesion and easy to clean coating. It contains anti fungal and anti bacterial additives.
<b>RECOMMENDED USES</b>	Expressions Revolution is recommended for interior decorations of surfaces like concrete, plaster, gypsum, wooden, design board etc. For creating a beautiful contrast broken silky pearl colour effect. By applying various Expressions Base coat colour contrast to Expressions Revolution can create many design patterns. It can be applied in variety of artistical patterns or designs.

### TECHNICAL DATA

<b>COLOUR (DRY FILM)</b>	As per Expressions Revolution shade card.
<b>FINISH ( DRY FILM)</b>	Pearlescent – Silky
<b>VOLUME SOLIDS (ASTM D2697)</b>	37.0 ± 2%
<b>SPECIFIC GRAVITY</b>	1.03 ± 0.03
<b>THEORETICAL SPREADING</b>	9.0 – 12.0 m <sup>2</sup> /Litre. (Depends on application method, film thickness & nature of surface).
<b>RECOMMENDED DFT (DRY FILM)</b>	40 – 30 Mirons/Coat
<b>RECOMMENDED WFT (WET FILM)</b>	110 – 80 Microns/Coat
<b>FLASH POINT</b>	Water Base

### DRYING TIME

Drying time @ 30°C (Temperature, humidity, air movement, film thickness and number of coats all affect the drying time.)	
<b>TOUCH DRY</b>	1 hour
<b>FULLY DRY</b>	4 – 6 hours



**ADVANTAGES**

<b>EXPRESSIONS REVOLUTION</b>	Environmentally friendly, Pure acrylic emulsion, Excellent adhesion, Easy to clean, Beautiful broken silky pearl colour effect, Artistic and elegant look, Good workability.
-------------------------------	--

**APPLICATION INSTRUCTION**

<b>SURFACE PREPARATION</b>	The surface on which Expressions Revolution is to be applied should be sound, clean, and free from oil, grease, and dust. If required, by using suitable putty, the surface should be leveled and made smoothen by sand paper.
----------------------------	--

**APPLICATION DATA**

<b>APPLICATION TOOL</b>	Sponge, Cotton cloth
<b>CLEANING/THINNING</b>	Water
<b>THINNER (VOLUME)</b>	Ready to use

**SYSTEM**

<b>RECOMMENDED SYSTEM</b>	Expressions Acrylic Primer	: 1 coat
	Expressions Base Coat	: 2 coats
	Expressions Revolution	: 1 coat

**METHOD OF APPLICATION**

<p>Apply one coat of Expressions Acrylic Primer (White), diluted with 10-15% water, by using roller and allow it to dry.</p> <p>Apply two coats of desired colour of Expressions Base Coat, diluted with 5-10% water, by using roller (give suitable recoating interval between each coat) and allow it to dry.</p> <p>Ensure, Expressions Revolution is uniformly mixed with a clean spatula or a mechanical mixer.</p> <p>Apply one coat of the chosen colour of Expressions Revolution pattern by laying the material uniformly with wet sponge/folded cotton piece. To avoid unpleasant effects and joints continue the decorating application without any overlaps. Apply a little pressure only to the application tool during application. Allow it to dry</p> <p>Apply approximately 1 m<sup>2</sup> of the surface with regular and repeated movements. Continue the application, once the area is completed.</p>
--



**EXPRESSIONS REVOLUTION  
DECORATIVE COATINGS**

**TECHNICAL DATA SHEET**

**NATIONAL/INTERNATIONAL TEST CERTIFICATES**

<b>Sr. No.</b>	<b>Test Description</b>	<b>Test Reference</b>	<b>Compliance</b>
1	VOC	USEPA 24	Local Regulatory Requirements

**ADDITIONAL DATA**

<b>SHELF LIFE @ 30°C</b>	6 months, in original sealed container, with proper storage conditions.
--------------------------	---

**HEALTH & SAFETY**

<b>SAFETY PRECAUTIONS</b>	Generally, most of the water based paints are quite safe to handle with due precautions. As a general rule, avoid skin and eye contact by wearing overalls, gloves, mask etc. Spillage on skin should immediately be removed by thorough washing with water and soap or suitable cleaner. Eye should be flushed with fresh water. Avoid inhalation of vapours and paint mist by wearing suitable mask. In the event of ingestion and eye contact, seek medical attention immediately. Painting must be carried out in well-ventilated area. Local safety regulations to be followed.
---------------------------	--

**STORAGE & HANDLING**

<b>STORAGE</b>	Store the paint in proper storage conditions as per the local regulations. Keep the paint container in sealed condition under shed, away from direct sunlight and extreme temperatures. Do not keep paint material near to any ignition sources. Do not put back the half or unused material back in original container, containing the supplied paint, to avoid contamination. Handle with care. Stir well before use.
----------------	---

**NOTE:** We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data.

This data sheet supersedes all previous issued.  
Issued: 0718